

What is claimed is:

1. A high power output vacuum electron device comprising:
a cathode for emitting a supply of electrons,
an anode for attracting said electrons, said anode being constructed to allow said
electrons to pass through said anode,
an RF generator circuit in the path of said electron beam for generating RF signal
energy in the presence of a high-voltage power source,
a magnet surrounding said anode and said RF generation circuit for focusing said
electrons into a collimated beam, and
a collector for receiving the collimated electron beam and for returning the
electrons to the cathode, said collector is a multi-stage depressed collector which is
shielded from the magnetic field from said magnet.
2. The vacuum electron device of Claim 1 wherein [the region of] said collector is free of
any magnetic fields such that the electron beam naturally disperses to evenly deposit said
electrons on [the] inner walls of said collector, said collector being thereby free of hot spots
due to uneven electron deposition thereon.
3. The vacuum electron device of Claim 1 wherein said collector is free of magnetic flux
reversals from said magnet such that the electron beam evenly disperses on said collector.

4. A vacuum electron device including a source of electrons, said electrons being formed into a narrow beam, and a collector for collecting said electrons, the improvement comprising:

a magnet surrounding and focusing said narrow beam, the magnetic flux of said magnet being parallel to and collinear with the centerline of said electron beam, said magnet having open pole pieces along said centerline to focus and drive said electron beam, said magnet having second open pole pieces adjacent to the area of said source of electrons to initially focus said electron beam, said magnet having no open pole pieces in the vicinity of said collector so that any magnetic flux from the magnet is directed back into the body of said magnet.

5. The vacuum electron device of Claim 4 wherein said collector includes an internal chamber, said electrons evenly dispersing within said internal chamber thereby eliminating any hot spots due to magnetically focused electrons.

6. The vacuum electron device of Claim 5 wherein said collector comprises a multi-stage depressed collector, each of said stages being connected to a different high-voltage supply such that electrons of different kinetic energies will impinge on the associated depressed collector.

7. A gun only magnet utilized in a multi-stage depressed collector high-energy vacuum electron device comprising:

could be a 17

a first pole piece region generating magnetic flux adjacent a cathode of said vacuum electron device to drive and initially focus electrons emitted from said cathode, and

a second pole piece region forming magnetic flux along the path of electrons to

5 focus said electrons into a narrow beam, said magnet having no pole piece in the region of said vacuum electron device where the electrons are collected and returned to said cathode.

008230-064479-062800

add B6